




TECHNICAL DATA SHEET - CST 0020/03 - 04/10/2013

GR 8888

T	°C	-100 +450 (1) / +650 (2)		
p	bar	200	20	40
V	m/s	1	3	30
pH		0 + 14 (3)		



- (1) With mild oxidizing media
- (2) With steam
- (3) Avoid the strong oxidizers
- (4) Avoid the product's use at the maximum temperature and pressure value associated without consult the manufacturer

Composition

- Rayon graphite yarns high carbon content
- Impregnated with colloidal graphite
- Passive inhibitor of corrosion

Features

GR8888 is a special packing braided with Rayon yarns high carbon content (99,5%). The yarns are flexible and insensitive to thermal cycles. Each yarn is impregnated with colloidal graphite reach of passive inhibitor of corrosion.

Applications

GR8888 it's a packing very high temperature resistant, showing minimal volume and weight loss, able to preserves the recovery over time. Suitable for Valve and Pump applications with all fluids and gases, excluded the strong oxidizers, combustion's gases and hot air over 450°C.

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	123,5	405	123,5	183,9
4,0	-	1,0	2,2	69,4	228	69,4	103,4
5,0	3/16	1,0	2,2	44,4	146	44,4	66,2
6,0	-	2,5	5,5	77,2	253	30,9	46,0
6,5	1/4	2,5	5,5	65,7	216	26,3	39,2
8,0	5/16	2,5	5,5	43,4	142	17,4	25,9
9,5	3/8	2,5	5,5	30,8	101	12,3	18,3
10,0	-	2,5	5,5	27,8	91	11,1	16,6
11,0	7/16	2,5	5,5	23,0	75	9,2	13,7
12,0	-	2,5	5,5	19,3	63	7,7	11,5
12,7	1/2	2,5	5,5	17,2	57	6,9	10,3
14,0	9/16	5,0	11,0	28,3	93	5,7	8,4
16,0	5/8	5,0	11,0	21,7	71	4,3	6,5
17,5	11/16	5,0	11,0	18,1	60	3,6	5,4
18,0	-	5,0	11,0	17,1	56	3,4	5,1
19,0	3/4	5,0	11,0	15,4	50	3,1	4,6
22,0	7/8	5,0	11,0	11,5	38	2,3	3,4
25,5	1	5,0	11,0	8,5	28	1,7	2,5

Packaged +/- 10 % in weight. Customized sizes and packaging are available on demand