






TECHNICAL DATA SHEET - CST 0300/02 - 19/09/2013

N 2609

(*)				
T	°C	-50 +250		
p	bar	60	40	20
V	m/s	1	3	10
pH		4 ÷ 10		



(*) Avoid the product's use at the maximum temperature and pressure value associated without consult the manufacturer

Composition

- Preox/Viscose yarns
- Graphite Powder
- Inert Lubricant

Features

CARRARA N 2609 has been developed for the purpose applications, offering a packing with very competitive price. Made with a blending of pre oxidized carbon and organic yarns, the packing is impregnated with graphite powder and lubricated with inert lubricant silicon free for high temperatures.

Applications

Suitable for purpose application with steam and mild industrial fluids.

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	92,6	304	92,6	137,9
4,0	-	1,0	2,2	52,1	171	52,1	77,6
5,0	3/16	1,0	2,2	33,3	109	33,3	49,7
6,0	-	2,5	5,5	57,9	190	23,1	34,5
6,5	1/4	2,5	5,5	49,3	162	19,7	29,4
8,0	5/16	2,5	5,5	32,6	107	13,0	19,4
9,5	3/8	2,5	5,5	23,1	76	9,2	13,8
10,0	-	2,5	5,5	20,8	68	8,3	12,4
11,0	7/16	2,5	5,5	17,2	56	6,9	10,3
12,0	-	2,5	5,5	14,5	47	5,8	8,6
12,7	1/2	2,5	5,5	12,9	42	5,2	7,7
14,0	9/16	5,0	11,0	21,3	70	4,3	6,3
16,0	5/8	5,0	11,0	16,3	53	3,3	4,8
17,5	11/16	5,0	11,0	13,6	45	2,7	4,1
18,0	-	5,0	11,0	12,9	42	2,6	3,8
19,0	3/4	5,0	11,0	11,5	38	2,3	3,4
22,0	7/8	5,0	11,0	8,6	28	1,7	2,6
25,5	1	5,0	11,0	6,4	21	1,3	1,9
Packaged +/- 10% in weight Customized sizes and packaging are available on demand							