



# Forged Steel High-Pressure Fittings

## ELBOW 90°


### Description

Pressure: 2000Lbs,3000Lbs  
 Material: Forged Steel  
 Size Rate: from 1/4" to 6"  
 Standard:ASME B 16.11,JIS  
 Thread : NPT

- THREADED (ANSI/ASME B1.20.1-1992)
- ASME B16.11-1996



### Dimensions and weights



ASME B16.11-1996 - THREADED (ANSI/ASME B1.20.1-1992)

NW		3000 Lbs						6000 Lbs					
		øH	G	A	Min. Trhead		Weight Kg	øH	G	A	Min. Trhead		Weight
B	L <sub>2</sub>				L <sub>2</sub>	KgMin.							
<b>6</b>	1/8"	22	3,2	21	6,4	6,7	0,10	25	6,4	25	6,4	6,7	0,17
<b>8</b>	1/4"	25	3,3	25	8,1	10,2	0,14	33	6,6	28	8,1	10,2	0,30
<b>10</b>	3/8"	33	3,5	28	9,1	10,4	0,27	38	7,0	33	9,1	10,4	0,45
<b>15</b>	1/2"	38	4,1	33	10,9	13,6	0,41	46	8,2	38	10,9	13,6	0,72
<b>20</b>	3/4"	46	4,3	38	12,7	13,9	0,72	56	8,5	44	12,7	13,9	1,15
<b>25</b>	1"	56	5,0	44	14,7	17,3	1,03	62	9,9	51	14,7	17,3	1,61
<b>32</b>	1 1/4"	62	5,3	51	17,0	18,0	1,31	75	10,6	60	17,0	18,0	2,67
<b>40</b>	1 1/2"	75	5,6	60	17,8	18,4	2,21	84	11,1	64	17,8	18,4	3,20
<b>50</b>	2"	84	7,1	64	19,0	19,2	2,47	102	12,1	83	19,0	19,2	5,90
<b>65</b>	2 1/2"	102	7,7	83	23,6	28,9	4,53	121	15,3	95	23,6	28,9	9,88
<b>80</b>	3"	121	8,8	95	25,9	30,5	7,77	146	16,6	106	25,9	30,5	16,43
<b>100</b>	4"	152	11,2	114	27,7	33,0	13,27	152	18,7	114	27,7	33,0	