

TECHNICAL BULLETIN

The information provided is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.



"GIMME THE GREEN STUFF!"

DESCRIPTION

Slow drying, soft setting, non-hardening pipe thread compound. Recommended for on-site or assembly line work. Lead free. Non-toxic. Will not harden in can.

NO LEAKS / NO CALLBACKS

Will not dry out, stain, harden or separate. Non-toxic. Will not destroy the seals of valves or faucets. Wipes clean from hands easily.

CHARACTERISTICS

Jomar Seal "Gimme the Green Stuff" thread sealing compound is recommended for residential and commercial applications where cleanliness is essential. Non-seizing — breaks out easily without stripping, galling or damaging threads. Free of halogens. Not affected by oils, dilute caustics, or dilute acids. Use on all metal, PVC, CPVC, nylon and polypropylene threads.

TEMPERATURE/PRESSURE RANGES

Temperature Ranges: -50°F to 400°F; Flash Point 43°F
Brushable to -50°F
Pressure Ranges: Gases to 3,000 PSI
Liquids to 6,000 PSI



**CERTIFIED TO A.G.A. NO. 4-90
METAL THREADS ONLY FOR
USE WITH NATURAL & LP
(VAPOR STATE) GASES ONLY**

RECOMMENDED FOR USE ON:

- | | |
|-------------------------|-----------------------------|
| Acids, dilute | Hydraulic oils |
| Air, compressed gaseous | Inert Gasses |
| Ammonia | Jet Fuel (JP4, 5, 6) |
| Aliphatic Solvents | Kerosene |
| Brine | Liquefied Petroleum Gases |
| Carbon Dioxide | Manufactured Gases |
| Castor Oils | Mineral Oils |
| Caustic Alkali, dilute | Natural Gases |
| Diesel Fuel Oil | Nitrogen, Gaseous |
| Freons (all) | Petroleum Solvents |
| Gasoline | Steam lines |
| Heating Oils | Sugar, Liquid |
| Helium, Gaseous | Water, Potable, hot or cold |

NOT FOR USE ON OXYGEN OR ABS THREADS

DIRECTIONS

Stir before using. Clean oil, dirt, grease or any foreign material from threads. Apply only to male threads. Use on all metal, plastic, PVC or, Fiberglass CPVC, and NYLON threads.

MAY BE LEFT ON TRUCK OVERNIGHT IN WINTER WEATHER AND CAN BE BRUSHED WHEN PRODUCT IS EXPOSED TO BELOW 0°F TEMPERATURES WITH NO SEPARATION.

2 OZ., NO CHARGE, FIELD TEST SAMPLE... AVAILABLE UPON REQUEST.