

**TECHNICAL BULLETIN**

The information provided is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to the result, since the conditions of use are beyond our control. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.



**"GIMME THE WHITE STUFF!"™**

**DESCRIPTION**

All purpose **PTFE THREAD SEALING COMPOUND** that produces leakproof seals on threaded connections. Lubricates, seals and protects threads in an extensive variety of plumbing, heating and oil field threaded pipe connections over a wide range of services, temperatures and pressures.

**CONTAINS NO LEAD**

Will not dry out, stain, harden or separate. Non-toxic. Will not destroy the seals of valves or faucets. Wipes clean from hands easily.

**CHARACTERISTICS**

Jomar Seal PTFE thread sealing compound is recommended for residential and commercial applications where cleanliness is essential. Non-seizing — breaks out easily without stripping, galling or damaging threads. Free of halogens. Not affected by oils, dilute caustics or dilute acids.

**TEMPERATURE/PRESSURE RANGES**

**Temperature Ranges:** -50°F to 400°F; Flash Point 43°F  
Brushable to -50°F  
**Pressure Ranges:** Gases to 3,000 PSI  
Liquids to 8,000 PSI

**RECOMMENDED FOR USE ON:**

- |                         |                           |
|-------------------------|---------------------------|
| Acids, dilute           | Hydraulic oils            |
| Air, compressed gaseous | Inert Gasses              |
| Ammonia                 | Jet Fuel (JP4, 5, 6)      |
| Aliphatic Solvents      | Kerosene                  |
| Brine                   | Liquefied Petroleum Gases |
| Carbon Dioxide          | Manufactured Gases        |
| Castor Oils             | Mineral Oils              |
| Caustic Alkali, dilute  | Natural Gases             |
| Diesel Fuel Oil         | Nitrogen, gaseous         |
| Freons (all)            | Petroleum Solvents        |
| Gasoline                | Steam                     |
| Heating Oils            | Sugar, Liquid             |
| Helium, gaseous         | Water, (hot or cold)      |

**NOT FOR USE ON OXYGEN**

**DIRECTIONS**

Stir before using. Clean oil, dirt, grease or any foreign material from threads. Apply only to male threads. Use on all Metal, plastic, PVC, ABS, Fiberglass, CPVC and Nylon threads.

**MAY BE LEFT ON TRUCK OVERNIGHT IN WINTER WEATHER AND CAN BE BRUSHED WHEN PRODUCT IS EXPOSED TO BELOW ZERO TEMPERATURES WITH NO SEPARATION**